



Industrial Ethernet-Switch unmanaged, 10/100 Mbit

5-port, unmanaged, 10/100 Mbit

- Store-and-Forward architecture
- 10/100Base-T/TX, Full-/Half-Duplex (Autonegotiation)
- HP Auto MDI/MDI-X & IEEE 802.3u Auto crossover support
- 1 K MAC address lookup table
- 64 KByte memory for frame buffering
- IEEE 802.3x Full duplex flow control
- 1.4 Gbps high-performance memory bandwidth

The Helmholz unmanaged Ethernet switches are suitable for a variety of industrial applications because of their very compact design. The lightweight and tough industrial design is suitable for mounting on a DIN rail and can be easily integrated into your network. Once plugged in, it's ready for use thanks to the simple Plug & Play solution. The tool-free push-in connection for the power supply supports you.

With this variant of the unmanaged Ethernet-Switch, you can connect up to 5 Ethernet participants with 10 or 100 Mbps. If you would like to connect more participants, we recommend our 8-port unmanaged Ethernet Switch.

Technical specifications

General information	
Order number	700-840-5E501
Article name	Ethernet-Switch 5-port, unmanaged, 10/100Mbps
Scope of delivery	Ethernet 5-port switch with power supply plug, short manual
Dimensions (DxWxH)	32.5 x 48.5 x 80.5 mm
Weight	Approx. 110g
LAN interface	
Number	5
Type	10/100Base-T/TX, Full/Half-Duplex (Autonegotiation) Auto MDI/MDI-X; IEEE Autocrossover
Connection	RJ45
Transmission rate	10/100 Mbps
Status indicator	1 LEDs power display, 10 LEDs Ethernet status
Voltage supply	24 V DC (18...30 V DC)
Current draw	Max. 60 mA with 24 V DC
Power dissipation	1,5 W
Ambient conditions	
Ambient temperature	-25 °C ... +75 °C
Transport and storage temperature	-40 °C ... +85 °C
Relative air humidity	95 % r H without condensation

Pollution degree	2
Protection rating	IP20
Certifications	CE, UL
CE	
RoHS	Yes
REACH	Yes
UL	
UL	UL 61010-1/ UL 61010-2-201
Pollution degree	2
Voltage supply	DC 24 V (18 ... 30 VDC, SELV and limited energy circuit)
Altitude	Up to 2000 m
Temperature cable rating	87 °C